NSN 4140-00-821-5141

Vaneaxial Fan - Page 1 of 2

Stage Quantity:



View Online at https://aerobasegroup.com/nsn/4140-00-821-5141

| Speed Adjustments: |
|--|
| Single speed |
| Diameter: |
| 4.000 inches |
| Length: |
| 4.970 inches |
| Flow Direction: |
| Inward |
| Environmental Protection: |
| Explosion proof |
| Ambient Tempurature At Full Rated Power: |
| 32.0 degrees fahrenheit and 140.0 degrees fahrenheit |
| Operating Speed At Rated Capacity In Rpm: |
| 11000.0 |
| Electrical Connection Type: |
| Terminal |
| Static Pressure At Specificationified Air Flow Rate: |
| 2.0 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 1 flange |
| Rotation Direction For Which Designed: |
| Counterclockwise |
| Features Provided: |
| Nonsparking |
| Air Flow Rate: |
| 140.0 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 115.0 ac |
| Prime Mover Power Rating: |
| 0.150 horsepower |
| Housing Inside Diameter: |
| 4.280 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |

NSN 4140-00-821-5141

Vaneaxial Fan - Page 2 of 2



| Phase: |
|-------------------------|
| Three |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Aluminum housing |
| Quantity: |
| 1 |
| Surface Treatment: |
| Lacquer housing outside |
| Style Designator: |
| Fixed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A087a0