

View Online at <https://aerobasegroup.com/nsn/4140-00-821-5734>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

2.468 inches

Flow Direction:

Inward

Environmental Protection:

Corrosion resistant and explosion proof and moisture resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-65.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

12500.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

91.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac or 200.0 ac

Prime Mover Power Rating:

63.0 watts

Housing Inside Diameter:

2.812 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0