

View Online at <https://aerobasegroup.com/nsn/4140-00-823-9194>

**Speed Adjustments:**

Single speed

**Length:**

1.730 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Dustproof and explosion proof and humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 71.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

11860.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

1.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

80.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.113 horsepower

**Housing Inside Diameter:**

3.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-5557, type 4 military specification single treatment response

**Style Designator:**

Fixed

**Test Data Document:**

97942-128c397h01 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5557 spec.