

View Online at <https://aerobasegroup.com/nsn/4140-00-826-3823>

Speed Adjustments:

Single speed

Diameter:

8.000 inches

Length:

6.750 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and fungus proof and humidity proof and shock proof and vibration proof and salt spray resistant

Operating Speed At Rated Capacity In Rpm:

3800.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

740.0 cubic feet per minute

Voltage In Volts And Current Type:

208.0 ac

Prime Mover Power Rating:

0.180 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Class f (150 degrees c) insulation, unitec-500 lubricant

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Anodize

Style Designator:

Fixed

Test Data Document:

89661-138c051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0