

View Online at <https://aerobasegroup.com/nsn/4140-00-838-5976>

**Speed Adjustments:**

Single speed

**Length:**

1.625 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Dustproof

**Ambient Temperature At Full Rated Power:**

43.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

1750.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

52.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.009 horsepower

**Housing Inside Diameter:**

4.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Sleeve

**Phase:**

Single

**Special Features:**

4.690 in. Sq flange each end of venturi tube

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Plastic phenolic housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0