NSN 4140-00-843-1300

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-843-1300

| Stage Quantity: |
|--|
| 1 |
| Speed Adjustments: |
| Single speed |
| Diameter: |
| 4.500 inches |
| Length: |
| 4.250 inches |
| Flow Direction: |
| Inward |
| Environmental Protection: |
| Dustproof |
| Ambient Tempurature At Full Rated Power: |
| -54.0 degrees celsius and 85.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 8000.0 |
| Electrical Connection Type: |
| Wire lead |
| Static Pressure At Specificationified Air Flow Rate: |
| 3.1 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 2 flange |
| Rotation Direction For Which Designed: |
| Counterclockwise |
| Air Flow Rate: |
| 260.000 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 208.0 ac |
| Prime Mover Power Rating: |
| 0.125 horsepower |
| Housing Inside Diameter: |
| 5.500 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |
| Phase: |
| Three |

NSN 4140-00-843-1300

Vaneaxial Fan - Page 2 of 2

Frequency In Hertz:

400.0

Material:

Steel

Quantity:

1

Surface Treatment:

Zinc housing outside

Style Designator:

Fixed

Test Data Document:

02769-8939970-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

