

View Online at <https://aerobasegroup.com/nsn/4140-00-844-1791>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

4.250 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Explosion proof

**Ambient Temperature At Full Rated Power:**

54.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

7400.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

3.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

260.0 cubic feet per minute

**Voltage In Volts And Current Type:**

208.0 ac

**Prime Mover Power Rating:**

0.125 horsepower

**Housing Inside Diameter:**

4.531 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Surface Treatment:**

Enamel

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0