

View Online at <https://aerobasegroup.com/nsn/4140-00-844-1791>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

4.250 inches

Flow Direction:

Outward

Environmental Protection:

Explosion proof

Ambient Temperature At Full Rated Power:

54.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

7400.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

3.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

6 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

260.0 cubic feet per minute

Voltage In Volts And Current Type:

208.0 ac

Prime Mover Power Rating:

0.125 horsepower

Housing Inside Diameter:

4.531 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0