

View Online at <https://aerobasegroup.com/nsn/4140-00-849-0403>

Speed Adjustments:

Single speed

Width:

2.625 inches

Length:

3.344 inches

Flow Direction:

Outward

Environmental Protection:

Explosion proof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-65.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11000.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

62.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.033 horsepower

Housing Inside Diameter:

2.422 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Height:

2.625 inches

Material:

Aluminum blade

Surface Treatment:

Anodize blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0