

View Online at <https://aerobasegroup.com/nsn/4140-00-851-9319>

**Speed Adjustments:**

Three speed

**Diameter:**

16.000 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Dustproof

**Ambient Temperature At Full Rated Power:**

40.0 degrees celsius

**Electrical Connection Type:**

Cord w/attached plug

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

4000.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

85.0 watts

**Phase:**

Single

**Special Features:**

Oscillating

**Frequency In Hertz:**

60.0

**Height:**

27.500 inches

**Material:**

Steel housing

**Quantity:**

1

**Surface Treatment:**

Enamel housing

**Style Designator:**

Fixed

**Test Data Document:**

81348-wf-00101 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Or Standard:**

1 type and 3 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0