

View Online at <https://aerobasegroup.com/nsn/4140-00-853-2138>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

4.469 inches

**Diameter:**

4.000 inches

**Length:**

6.344 inches

**Environmental Protection:**

Humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3350.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

1.031 inches

**Outlet Inside Height:**

2.281 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

72.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.062 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical up

**Phase:**

Single

**Height:**

6.062 inches

**Material:**

Steel

**Quantity:**

1

**Surface Treatment:**

Zinc blade

**Surface Treatment Specification:**

Qq-z-325, type 2, cl2 federal specification single treatment response

**Style Designator:**

Fixed, inverted, rectangular outlet

**Test Data Document:**

13499-009-1556-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0