

View Online at <https://aerobasegroup.com/nsn/4140-00-853-2138>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

4.469 inches

Diameter:

4.000 inches

Length:

6.344 inches

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3350.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

1.031 inches

Outlet Inside Height:

2.281 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 threaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

72.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.062 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Single

Height:

6.062 inches

Material:

Steel

Quantity:

1

Surface Treatment:

Zinc blade

Surface Treatment Specification:

Qq-z-325, type 2, cl2 federal specification single treatment response

Style Designator:

Fixed, inverted, rectangular outlet

Test Data Document:

13499-009-1556-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0