

View Online at <https://aerobasegroup.com/nsn/4140-00-860-7640>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

3.420 inches

Flow Direction:

Inward

Environmental Protection:

Dustproof and explosion proof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

20500.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

62.000 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.160 horsepower

Housing Inside Diameter:

Between 2.610 inches and 2.650 inches

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A087a0