

View Online at <https://aerobasegroup.com/nsn/4140-00-862-2835>

**Speed Adjustments:**

Single speed

**Length:**

1.470 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Moisture resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 100.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

19500.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

3 lug

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

Between 55.000 cubic feet per minute and 60.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.050 horsepower

**Housing Inside Diameter:**

1.891 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Surface Treatment:**

Enamel

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0