

View Online at <https://aerobasegroup.com/nsn/4140-00-873-3437>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

3.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Explosion proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 71.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

12000.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

86.0 cubic feet per minute

**Voltage In Volts And Current Type:**

204.0 ac

**Prime Mover Power Rating:**

400.000 watts

**Housing Inside Diameter:**

4.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Surface Treatment:**

Anodize housing inside

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0