

View Online at <https://aerobasegroup.com/nsn/4140-00-873-3448>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

2.718 inches

Length:

2.250 inches

Flow Direction:

Outward

Environmental Protection:

Explosion proof and humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

20500.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

140.0 cubic feet per minute

Voltage In Volts And Current Type:

104.0 ac

Prime Mover Power Rating:

0.111 horsepower

Housing Inside Diameter:

2.812 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Cadmium blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0