

View Online at <https://aerobasegroup.com/nsn/4140-00-873-3448>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

2.718 inches

**Length:**

2.250 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Explosion proof and humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

71.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

20500.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

140.0 cubic feet per minute

**Voltage In Volts And Current Type:**

104.0 ac

**Prime Mover Power Rating:**

0.111 horsepower

**Housing Inside Diameter:**

2.812 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Cadmium blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0