

View Online at <https://aerobasegroup.com/nsn/4140-00-875-9846>

Speed Adjustments:

Single speed

Width:

6.438 inches

Length:

8.625 inches

Environmental Protection:

Fungus proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3000.0

Electrical Connection Type:

Wire lead

Outlet Inside Height:

2.281 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 bracket and 3 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

300.0 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

240.0 ac

Prime Mover Power Rating:

0.563 horsepower

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Special Features:

Positioning when mtg by special bracket determines discharge blast direction

Height:

15.625 inches

Material:

Steel housing

Quantity:

1

Surface Treatment:

Enamel housing outside

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0