

View Online at <https://aerobasegroup.com/nsn/4140-00-875-9846>

**Speed Adjustments:**

Single speed

**Width:**

6.438 inches

**Length:**

8.625 inches

**Environmental Protection:**

Fungus proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3000.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Height:**

2.281 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 bracket and 3 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

300.0 cubic feet per minute

**Outlet Location:**

Bottom or top

**Voltage In Volts And Current Type:**

240.0 ac

**Prime Mover Power Rating:**

0.563 horsepower

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Single

**Special Features:**

Positioning when mtg by special bracket determines discharge blast direction

**Height:**

15.625 inches

**Material:**

Steel housing

**Quantity:**

1

**Surface Treatment:**

Enamel housing outside

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0