NSN 4140-00-879-6418

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-879-6418

| Speed Adjustments: |
|--|
| Single speed |
| Length: |
| 1.500 inches |
| Flow Direction: |
| Outward |
| Ambient Tempurature At Full Rated Power: |
| 125.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 10200.0 |
| Electrical Connection Type: |
| Terminal block |
| Static Pressure At Specificationified Air Flow Rate: |
| 0.0 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 3 threaded insert |
| Rotation Direction For Which Designed: |
| Counterclockwise |
| Air Flow Rate: |
| 28.0 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 115.0 ac |
| Prime Mover Power Rating: |
| 11.000 watts |
| Housing Inside Diameter: |
| 2.000 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |
| Phase: |
| Single |
| Frequency In Hertz: |
| 400.0 |
| Material: |
| Aluminum alloy |
| Surface Treatment: |
| Enamel baked |
| |

NSN 4140-00-879-6418

Vaneaxial Fan - Page 2 of 2



Surface Treatment Specification:

Black, 98, the prestolite co. Mfr ref single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A087a0