

View Online at <https://aerobasegroup.com/nsn/4140-00-880-0759>

**Speed Adjustments:**

Single speed

**Diameter:**

3.000 inches

**Length:**

2.800 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Corrosion resistant and moisture resistant and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

7700.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 rack and 3 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

70.000 cubic feet per minute

**Voltage In Volts And Current Type:**

208.0 ac

**Prime Mover Power Rating:**

0.022 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Anodize

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0