

View Online at <https://aerobasegroup.com/nsn/4140-00-888-4160>

Speed Adjustments:

Single speed

Length:

Between 1.515 inches and 1.640 inches

Flow Direction:

Inward

Ambient Temperature At Full Rated Power:

65.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

21500.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

122.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.054 horsepower

Housing Inside Diameter:

3.064 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum

Unpackaged Unit Weight:

0.406 pounds

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.