NSN 4140-00-902-7744



Vaneaxial Fan - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4140-00-902-7744 Stage Quantity: **Speed Adjustments:** Single speed Length: 1.468 inches Flow Direction: Inward **Environmental Protection:** Humidity proof and salt spray resistant and shock proof and vibration proof **Ambient Tempurature At Full Rated Power:** -55.0 degrees celsius and 100.0 degrees celsius **Operating Speed At Rated Capacity In Rpm:** 10000.0 **Electrical Connection Type: Terminal** Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Mounting Facility Type And Quantity:** 1 flange and 3 threaded hole **Rotation Direction For Which Designed:** Clockwise Air Flow Rate: 32.0 cubic feet per minute **Voltage In Volts And Current Type:** 115.0 ac **Prime Mover Power Rating:** 10.0 watts **Housing Inside Diameter:** 1.891 inches **Prime Mover Drive Shaft Bearing Type:** Ball Phase: Single

400.0

Frequency In Hertz:

NSN 4140-00-902-7744

Vaneaxial Fan - Page 2 of 2



ate	

Aluminum

Surface Treatment:

Enamel lusterless

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A087a0