

View Online at <https://aerobasegroup.com/nsn/4140-00-904-3357>

**Speed Adjustments:**

Single speed

**Length:**

2.000 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Dustproof and explosion proof and fungus resistant and humidity proof and shock proof and vibration proof and salt spray resistant

**Ambient Temperature At Full Rated Power:**

100.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

10800.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 clamp ring

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

185.000 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.080 horsepower

**Housing Inside Diameter:**

3.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Unpackaged Unit Weight:**

1.000 pounds

**Surface Treatment:**

Enamel

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0