

View Online at <https://aerobasegroup.com/nsn/4140-00-904-3438>

**Speed Adjustments:**

Single speed

**Width:**

6.532 inches

**Length:**

8.625 inches

**Environmental Protection:**

Humidity proof and shock proof and spray proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-28.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2900.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

2.109 inches

**Outlet Inside Height:**

3.000 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 6 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Inlet cone

**Air Flow Rate:**

Between 170.000 cubic feet per minute and 272.000 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.382 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical up

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Height:**

10.000 inches

**Material:**

Steel blade

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, inverted, rectangular outlet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0