

View Online at <https://aerobasegroup.com/nsn/4140-00-904-3438>

Speed Adjustments:

Single speed

Width:

6.532 inches

Length:

8.625 inches

Environmental Protection:

Humidity proof and shock proof and spray proof and vibration proof

Ambient Temperature At Full Rated Power:

-28.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

2900.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

2.109 inches

Outlet Inside Height:

3.000 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 6 threaded hole

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Inlet cone

Air Flow Rate:

Between 170.000 cubic feet per minute and 272.000 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.382 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Three

Frequency In Hertz:

60.0

Height:

10.000 inches

Material:

Steel blade

Surface Treatment:

Zinc blade

Style Designator:

Fixed, inverted, rectangular outlet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0