

View Online at <https://aerobasegroup.com/nsn/4140-00-910-3425>

Speed Adjustments:

Single speed

Width:

8.581 inches

Length:

7.781 inches

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-12.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3000.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

1.422 inches

Outlet Inside Height:

2.750 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

160.000 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.014 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Special Features:

Positioning when mtg determines discharge blast direction, class f insulation motor windings

Frequency In Hertz:

60.0

Height:

10.000 inches

Material:

Steel

Surface Treatment:

Zinc housing outside and enamel housing outside

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0