

View Online at <https://aerobasegroup.com/nsn/4140-00-913-4209>

**Stage Quantity:**

2

**Speed Adjustments:**

Single speed

**Length:**

Between 2.585 inches and 2.615 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Dustproof and humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

21000.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim and 6 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

60.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.214 horsepower

**Housing Inside Diameter:**

2.812 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Surface Treatment:**

Anodize blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0