

View Online at <https://aerobasegroup.com/nsn/4140-00-919-9596>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

8.540 inches

**Diameter:**

4.500 inches

**Length:**

7.810 inches

**Environmental Protection:**

Humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-30.0 degrees celsius and 50.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3100.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

3.219 inches

**Outlet Inside Height:**

3.594 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

335.0 cubic feet per minute

**Outlet Location:**

Bottom and top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.321 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Single

**Special Features:**

Adjustable direction of discharge, class a insulation motor windings

**Height:**

8.720 inches

**Material:**

Steel

**Quantity:**

1

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0