

View Online at <https://aerobasegroup.com/nsn/4140-00-919-9598>

Speed Adjustments:

Single speed

Width:

8.540 inches

Length:

7.810 inches

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-30.0 degrees celsius and 50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3100.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

3.219 inches

Outlet Inside Height:

3.594 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 threaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

335.0 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.321 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Special Features:

Adjustable direction of discharge, class a insulation motor windings

Frequency In Hertz:

50.0 and 60.0

Height:

8.720 inches

Material:

Steel

Surface Treatment:

Zinc blade

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0