

View Online at <https://aerobasegroup.com/nsn/4140-00-922-0876>

**Speed Adjustments:**

Single speed

**Diameter:**

2.781 inches

**Length:**

1.346 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

25.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

12500.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 ring

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

63.000 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.024 horsepower

**Housing Inside Diameter:**

3.064 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Anodize and enamel

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification 1st treatment response and mil-e-5557, type 4 military specification 2nd treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.