

View Online at <https://aerobasegroup.com/nsn/4140-00-922-0964>

Speed Adjustments:

Single speed

Width:

4.690 inches

Diameter:

4.500 inches

Length:

1.500 inches

Flow Direction:

Inward

Environmental Protection:

Moisture resistant

Ambient Temperature At Full Rated Power:

-40.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3265.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

112.000 cubic feet per minute

Voltage In Volts And Current Type:

26.5 ac

Prime Mover Power Rating:

0.025 horsepower

Housing Inside Diameter:

4.687 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

60.0

Height:

4.690 inches

Material:

Plastic polycarbonate blade

Surface Treatment:

Enamel housing

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response housing

Style Designator:

Fixed

Test Data Document:

49956-462665-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.