

View Online at <https://aerobasegroup.com/nsn/4140-00-922-1247>

**Speed Adjustments:**

Single speed

**Length:**

2.281 inches

**Flow Direction:**

Reversible

**Environmental Protection:**

Shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 100.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

19500.0

**Electrical Connection Type:**

Connector

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

3 clamp ring

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

185.000 cubic feet per minute

**Voltage In Volts And Current Type:**

28.0 dc

**Prime Mover Power Rating:**

34.000 watts

**Housing Inside Diameter:**

3.750 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Material:**

Aluminum housing

**Surface Treatment:**

Enamel housing outside

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0