

View Online at <https://aerobasegroup.com/nsn/4140-00-925-5188>

Speed Adjustments:

Single speed

Diameter:

6.858 inches

Length:

2.500 inches

Flow Direction:

Reversible

Environmental Protection:

Fungus resistant and humidity proof and moisture resistant and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3200.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

265.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.032 horsepower

Housing Inside Diameter:

7.000 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

60.0

Material:

Aluminum alloy

Quantity:

1

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A087a0

Mil-std (military Standard):

Mil-b-23071 spec.