

View Online at <https://aerobasegroup.com/nsn/4140-00-926-9648>

**Length:**

Between 7.250 inches and 7.500 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Fungus resistant and humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-40.0 degrees celsius and 65.6 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3500.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

2 flange and 16 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

775.05 cubic feet per minute

**Voltage In Volts And Current Type:**

28.0 dc

**Housing Inside Diameter:**

9.120 inches

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-430, alloy 6065 federal specification single material response blade

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Fixed

**Test Data Document:**

80063-sm-c-603032 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.