

View Online at <https://aerobasegroup.com/nsn/4140-00-926-9648>

Length:

Between 7.250 inches and 7.500 inches

Flow Direction:

Outward

Environmental Protection:

Fungus resistant and humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-40.0 degrees celsius and 65.6 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3500.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

2 flange and 16 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

775.05 cubic feet per minute

Voltage In Volts And Current Type:

28.0 dc

Housing Inside Diameter:

9.120 inches

Material:

Aluminum alloy

Material Specification:

Qq-a-430, alloy 6065 federal specification single material response blade

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Fixed

Test Data Document:

80063-sm-c-603032 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.