

View Online at <https://aerobasegroup.com/nsn/4140-00-936-9189>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

4.000 inches

Length:

5.800 inches

Flow Direction:

Inward

Environmental Protection:

Dustproof and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 95.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

9000.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

200.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac or 200.0 ac

Prime Mover Power Rating:

0.770 horsepower

Housing Inside Diameter:

4.875 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Finger guard w/3/8 in. Maximum radial spacing

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Paint

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0