

View Online at <https://aerobasegroup.com/nsn/4140-00-939-8605>

**Speed Adjustments:**

Single speed

**Width:**

8.722 inches

**Length:**

8.000 inches

**Environmental Protection:**

Explosion proof and humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-65.0 degrees celsius and 160.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

24000.0

**Electrical Connection Type:**

Connector receptacle

**Outlet Inside Diameter:**

3.500 inches

**Static Pressure At Specificationified Air Flow Rate:**

18.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 clamp

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

260.0 cubic feet per minute

**Outlet Location:**

Bottom

**Voltage In Volts And Current Type:**

115.0 ac or 200.0 ac

**Prime Mover Power Rating:**

1.400 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Frequency In Hertz:**

50.0 and 60.0 and 400.0

**Height:**

8.055 inches

**Material:**

Steel blade

**Style Designator:**

Fixed, round outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0