

View Online at <https://aerobasegroup.com/nsn/4140-00-941-4098>

**Stage Quantity:**

1

**Diameter:**

Between 7.216 inches and 7.218 inches

**Length:**

Between 7.190 inches and 7.280 inches

**Flow Direction:**

Inward

**Operating Speed At Rated Capacity In Rpm:**

11400.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

12.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Mounting Facility Type And Quantity:**

1 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

901.000 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

2.750 horsepower

**Housing Inside Diameter:**

Between 7.190 inches and 7.280 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Magnesium alloy blade

**Material Specification:**

Qq-m-56 federal specification single material response blade

**Quantity:**

1

**Surface Treatment:**

Dichromate blade and primer blade and lacquer blade

**Style Designator:**

Fixed

**Reference Number Differentiating Characteristics:**

As differentiated by source control dwg no. 114e4041-2, fscm 77272

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A087a0