

View Online at <https://aerobasegroup.com/nsn/4140-00-946-5441>

Speed Adjustments:

Single speed

Width:

3.969 inches

Environmental Protection:

Corrosion resistant and humidity proof and salt spray resistant

Ambient Temperature At Full Rated Power:

-33.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3500.0

Electrical Connection Type:

Terminal block

Outlet Inside Diameter:

1.250 inches

Static Pressure At Specificationified Air Flow Rate:

0.2 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 threaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

10.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

9.5 watts

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Phase:

Single

Special Features:

One uf capacitor across terminals 2 and 3

Frequency In Hertz:

50.0 and 60.0

Material:

Steel

Surface Treatment:

Cadmium blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0