

View Online at <https://aerobasegroup.com/nsn/4140-00-946-5441>

**Speed Adjustments:**

Single speed

**Width:**

3.969 inches

**Environmental Protection:**

Corrosion resistant and humidity proof and salt spray resistant

**Ambient Temperature At Full Rated Power:**

-33.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3500.0

**Electrical Connection Type:**

Terminal block

**Outlet Inside Diameter:**

1.250 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.2 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

10.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

9.5 watts

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Single

**Special Features:**

One uf capacitor across terminals 2 and 3

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Steel

**Surface Treatment:**

Cadmium blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0