## NSN 4140-00-956-7626

Tubeaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-956-7626 **Speed Adjustments:** Single speed Length: 1.625 inches Flow Direction: Outward **Environmental Protection:** Explosion proof **Ambient Tempurature At Full Rated Power:** -54.0 degrees celsius and 125.0 degrees celsius **Operating Speed At Rated Capacity In Rpm:** 3750.0 **Electrical Connection Type:** Wire lead Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Mounting Facility Type And Quantity:** 2 rim **Rotation Direction For Which Designed:** Counterclockwise **Features Provided:** Nonsparking Air Flow Rate: 212.0 cubic feet per minute **Voltage In Volts And Current Type: Prime Mover Power Rating:** 0.040 horsepower **Prime Mover Drive Shaft Bearing Type:** 

**Housing Inside Diameter: 6.858** inches Ball Phase: Single Frequency In Hertz: 60.0

## NSN 4140-00-956-7626

Tubeaxial Fan - Page 2 of 2



NЛ	ate	ria	
IVI	ale	110	ı .

Aluminum housing

**Surface Treatment:** 

Enamel housing outside

Style Designator:

Fixed

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A087a0