

View Online at <https://aerobasegroup.com/nsn/4140-00-965-1208>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

3.016 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and humidity proof and shock proof and submersible and vibration proof

Ambient Temperature At Full Rated Power:

-40.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11000.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.6 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 threaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

43.0 cubic feet per minute

Voltage In Volts And Current Type:

114.0 ac or 140.0 ac

Prime Mover Power Rating:

0.040 horsepower

Housing Inside Diameter:

2.312 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

350.0 and 450.0

Material:

Aluminum

Surface Treatment:

Anodize

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0