

View Online at <https://aerobasegroup.com/nsn/4140-00-968-4504>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

2.400 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-65.0 degrees celsius and 160.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

11000.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 clamp

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

72.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.014 horsepower

**Housing Inside Diameter:**

2.809 inches

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Surface Treatment:**

Anodize housing outside

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0