

View Online at <https://aerobasegroup.com/nsn/4140-00-968-7367>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

2.000 inches

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

-45.0 degrees fahrenheit and 145.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

10000.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 4 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

27.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.134 horsepower

**Housing Inside Diameter:**

2.044 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2, cl 1 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.