

View Online at <https://aerobasegroup.com/nsn/4140-00-981-8580>

Speed Adjustments:

Single speed

Diameter:

Between 4.469 inches and 4.531 inches

Length:

3.380 inches

Flow Direction:

Inward

Environmental Protection:

Explosion proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 62.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3300.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 threaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

265.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.017 horsepower

Housing Inside Diameter:

Between 4.593 inches and 4.655 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

60.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.