

View Online at <https://aerobasegroup.com/nsn/4140-00-986-9734>

**Speed Adjustments:**

Single speed

**Width:**

8.120 inches

**Length:**

8.800 inches

**Environmental Protection:**

Shock proof and vibration proof and salt spray resistant

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2500.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

4.060 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

345.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

208.0 ac

**Prime Mover Power Rating:**

260.0 watts

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical up

**Phase:**

Three

**Special Features:**

Max operating speed rated at 3500.0 rpm

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Steel

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0