

View Online at <https://aerobasegroup.com/nsn/4140-00-988-3143>

**Speed Adjustments:**

Single speed

**Width:**

9.750 inches

**Length:**

8.719 inches

**Environmental Protection:**

Moisture resistant and shock proof and salt spray resistant and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2950.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

3.188 inches

**Outlet Inside Height:**

4.750 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

460.0 cubic feet per minute

**Outlet Location:**

Bottom or top

**Voltage In Volts And Current Type:**

208.0 ac

**Prime Mover Power Rating:**

0.415 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Three

**Frequency In Hertz:**

50.0 and 60.0

**Height:**

7.812 inches

**Material:**

Steel

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0