

View Online at <https://aerobasegroup.com/nsn/4140-00-990-3311>

Speed Adjustments:

Single speed

Width:

4.688 inches

Length:

1.500 inches

Flow Direction:

Inward

Operating Speed At Rated Capacity In Rpm:

3300.0

End Application:

W/s: spruance class dd (963); snap i, an/uyk-6 (v); sturgeon class ssn (637); ticonderoga class cg (47); deep submergence system programs (dssp); defense meteorological satellite program (dmisp); teletype, model 28; missile, tomahawk; los angeles class ssn (688)

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

117.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.016 horsepower

Housing Inside Diameter:

4.500 inches

Phase:

Single

Special Features:

12.000 in. Wire leads

Frequency In Hertz:

50.0 and 60.0

Height:

4.688 inches

Material:

Plastic blade

Surface Treatment:

Enamel housing outside

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0