

View Online at <https://aerobasegroup.com/nsn/4140-00-993-0071>

**Speed Adjustments:**

Single speed

**Width:**

10.060 inches

**Length:**

6.940 inches

**Environmental Protection:**

Humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3500.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

2.720 inches

**Outlet Inside Height:**

2.500 inches

**Static Pressure At Specificationified Air Flow Rate:**

1.7 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

8 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

375.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

200.0 watts

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Height:**

6.310 inches

**Material:**

Aluminum housing

**Surface Treatment:**

Enamel housing outside

**Style Designator:**

Fixed, dual impeller, rectangular outlet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0